

PSC No. 1 – Water
UNITED WATER NEW ROCHELLE INC.
Initial Effective Date: January 1, 2014

Leaf No. 20
Revision: 1
Superseding Revision: 0

GENERAL INFORMATION

- (f) Any repairs or maintenance necessary on the Customer's service pipe or any pipe or fixture in or upon the Customer's premises shall be performed by the Customer at his expense and risk.
- (g) The Customer shall notify the Company promptly of any leak, defect or damage affecting the service pipe between the property line and the point where metered.
- (h) The Customer shall install a **valve** of a type approved by the Company on his service pipe immediately adjacent to the house side of the meter, and so located to be readily accessible to the occupants.

12. PLUMBING WORK MUST BE APPROVED BY COMPANY:

- (a) All plumbing work done on Customer's service pipes between the property line and the meter shall be submitted for the inspection of the Company, and no underground work shall be covered up until inspected and approved by the Company.

13. CROSS CONNECTIONS NOT ALLOWED:

- (a) No pipe or fixtures connected with the mains of the Company shall also be connected with pipes or fixtures supplied with water from any other source, unless specifically approved by the Department of Health of the State of New York.

14. METER AND METER INSTALLATIONS:

- (a) The Company shall have the right to determine the type and size of meter to be installed.
- (b) Meters will be furnished, installed and removed by the Company and shall remain its property.
- (c) The Customer shall provide at his expense a readily accessible and protected location for the installation of a meter at such a point as will control the entire supply to the premise, which location must be acceptable to the Company as most convenient for its service.
- (d) **When the Company requires that meters shall be installed outside of a building on customer's or private property, the meter shall be placed in a convenient meter pit, vault, or suitable and approved above ground heated meter structure, any and all of which are often referred to as the meter housing. The meter housing shall be located in an accessible place away from the terraces, fences, paved areas, other structures or any location which would create a hazard to vehicles, pedestrians or Company personnel accessing the meters. The meter housing shall be frost-proof and either well drained or watertight and shall be provided with a strong cover fastened with a convenient locking device. The cover shall be kept clear of snow, ice, dirt or any other objects which might prevent easy access for reading, inspecting, testing, changing and making**