

PSC NO: 8 GAS  
NATIONAL FUEL GAS DISTRIBUTION CORPORATION  
INITIAL EFFECTIVE DATE: 02/01/12

LEAF: 37.2  
REVISION: 0  
SUPERSEDING REVISION:

## GENERAL INFORMATION

### II. 7. METERS AND REGULATORS - Continued

#### g. Gas Quality Requirements for Production Facilities

Gas which is received by the Company shall not contain more than:

- (a) seven (7) pounds of water (H<sub>2</sub>O) in a vapor state per million cubic feet of gas;
- (b) three tenths (0.3) of a grain of hydrogen sulfide (H<sub>2</sub>S) per one hundred (100) feet of gas;
- (c) twenty (20) grains of total sulphur (S) per one hundred (100) cubic feet of gas;
- (d) four percent (4%) by volume of a combined total of carbon dioxide (CO<sub>2</sub>) and nitrogen (N<sub>2</sub>) components provided, however, that the total carbon dioxide (CO<sub>2</sub>) content shall not exceed two percent (2%) volume;
- (e) two tenths of one percent (0.2%) by volume of oxygen (O<sub>2</sub>). Customer further agrees to make every effort to keep the gas completely free of oxygen (O<sub>2</sub>).

Minimum heat content of gas received by the Company shall be one thousand British Thermal Units (1,000 BTU) per cubic foot (dry).

### 8. METER READING, BILLING AND COLLECTION

#### a. Meters and Billing Period

At the option of the Company, meters shall be read either monthly or bi-monthly. If the meter reading of a Customer is for a consumption period greater or less than a billing month, the stated rates shall apply pro-rata to the nearest full day of usage.

Issued by A. M. Cellino, President, 6363 Main Street, Williamsville, NY 14221  
(Name of Officer, Title, Address)