

PSC NO: 214 ELECTRICITY
NIAGARA MOHAWK POWER CORPORATION
INITIAL EFFECTIVE DATE: NOVEMBER 16, 2009

LEAF: 22
REVISION: 10
SUPERSEDING REVISION: 9

SERVICE CLASSIFICATION NO. 2 (Continued)

Table 4 - Luminaire Charge

<u>Luminaire Type</u>	<u>Annual Luminaire Charge, per unit (\$)</u>					
	<u>70</u>	<u>100</u>	<u>Lamp Size (Watts)</u>		<u>250</u>	<u>400</u>
			<u>150</u>	<u>175</u>		
Aspen Grove	----	73.46	59.93	59.93	80.00	79.59
Central Park	----	117.11	----	108.59	----	----
Coach	----	73.46	59.93	59.93	80.00	79.59
Delaware Park	----	----	184.60	184.60	227.88	227.88
Delaware Park Pedestrian	154.32	156.96	----	----	----	----
Edgewater	----	121.88	127.24	127.24	----	----
Edison	----	73.46	59.93	59.93	80.00	79.59
Floodlight	----	----	----	----	54.10	56.94
Roadway	46.20	46.09	47.12	47.12	54.17	54.17
Setback	----	----	----	----	102.36	102.36
Shoebox	----	73.46	59.93	59.93	80.00	79.59
Traditional	----	73.46	59.93	59.93	80.00	79.59
Underpass	79.97	79.97	80.79	80.79	----	----
Williamsville	91.86	91.86	110.28	110.28	----	----

3. Pole/Standard Charge:

The annual pole or standard charges per unit are presented below in Table 5. A pole or standard is the support structure for the luminaire. Poles are constructed of wood and are most commonly used for overhead supplied service. Standards are constructed of metal or composite material, can be decorative, and are typically used for underground supplied service. The pole/standard charges are determined by the type of pole or standard and its height.

Table 5 - Pole/Standard Charge

<u>Pole/Standard Type</u>	<u>Annual Pole/Standard Charge, per unit</u>	<u>Annual Charge (\$)</u>
Pole – for OH Service		
Wood - distribution (existing)		No Charge
Wood - street lighting (new, includes one (1) span)		97.06
Electric distribution line extension consisting of more than one (1) span		See Note below
Standard – (over 16 ft.), for UG or URD Service		
Aluminum – anchor base (AB)		234.07
Aluminum – anchor base (AB, heavy duty)		277.35
Aluminum – anchor base (AB, square)		473.42
Fiberglass – anchor base (AB)		159.92
Standard – (16 ft. and under), for UG or URD Service		
Aluminum – anchor base (AB)		100.51
Fiberglass – anchor base (AB)		62.18
Fiberglass – direct embedded (DE)		85.46

Issued by Thomas B. King, President, Syracuse, NY